

Vertical Rough-terrain Forklifts

Model	Base Cap.	Max Lift Height	Cap. Max. Fork Height	Drive Config.	Outside Turn Radius	GVW	HP
TS 6-22	6,000	28'	1,500	2WD-2WS	13' 5"	11,800	80
TS 8-22	8,000	28'	1,750	2WD-2WS	13' 5"	13,000	80
TS 10-22	10,000	22'	3,000	2WD-2WS	13' 6"	18,500	80
TS 12-22	12,000	22'	3,000	2WD-2WS	15'	19,000	105
TS 14-22	14,000	22'	3,000	2WD-2WS	15'	22,500	105
TS 16-22	16,000	20'	3,200	2WD-2WS	---	25,500	133
TS 18-22	18,000	20'	3,500	2WD-2WS	---	28,600	133
TS 20-22	20,000	20'	4,000	2WD-2WS	---	30,000	133
TS 22-22	22,000	18'	3,500	2WD-2WS	---	32,500	165
TS 24-22	24,000	18'	3,500	2WD-2WS	---	---	165
TS 26-22	26,000	18'	4,500	2WD-2WS	---	---	165
TS 28-22	28,000	16'	9,000	2WD-2WS	---	---	165
TS 30-22	30,000	16'	12,000	2WD-2WS	---	---	165
TS 6-44	6,000	28'	1,800	4WD-4WS	12' 2"	13,800	90
TS 8-44	8,000	38'	1,800	4WD-4WS	12' 6"	15,700	90
TS 10-44	10,000	30'	2,200	4WD-4WS	13'	17,500	90
TS 12-44	12,000	30'	2,300	4WD-4WS	13'	19,800	105
TS 14-44	14,000	22'	4,000	4WD-4WS	13'	23,100	105
TS 16-44	16,000	20'	4,200	4WD-4WS	14'	26,400	133
TS 18-44	18,000	20'	5,000	4WD-4WS	14' 6"	29,700	133
TS 20-44	20,000	20'	6,000	4WD-4WS	14' 6"	33,000	165
TS 22-44	22,000	18'	6,100	4WD-4WS	---	---	165
TS 24-44	24,000	18'	8,000	4WD-4WS	---	---	165
TS 26-44	26,000	18'	9,000	4WD-4WS	---	---	165
TS 28-44	28,000	16'	10,000	4WD-4WS	---	---	165
TS 30-44	30,000	16'	20,000	4WD-4WS	---	---	165
TS 6-42	6,000	32'	1,500	4WD-2WS	14'	13,800	80
TS 8-42	8,000	32'	1,750	4WD-2WS	14'	14,500	80
TS 10-42	10,000	22'	5,000	4WD-2WS	14' 5"	17,900	90
TS 12-42	12,000	22'	5,000	4WD-2WS	14' 5"	19,800	90

Telescopic Handler

TL 6-44-36	6,000	36'	6,000	4WD-4WS	13'	19,500	108
TL 6-44-42	6,000	42'	4,000	4WD-4WS	13'	20,300	108
TL 8-44-36	8,000	36'	6,000	4WD-4WS	13'	20,800	108
TL 8-44-42	8,000	42'	6,000	4WD-4WS	13'	21,500	108
TL 16-44-34	16,000	34'	8,000	4WD-4WS	19'	36,000	165
TL 16-22-25	16,000	25'	10,000	2WD-2WS	10' 8"	38,000	122
TL 20-44-34	20,000	34'	10,000	4WD-4WS	19'	45,000	165
TL 20-22-25	20,000	25'	16,000	2WD-2WS	10' 8"	43,200	122